

MARKED-UP COPY OF SUBSTITUTE SPECIFICATION

1AP20 Rec'd PCT/PTO 03 MAY 2006

TITLE OF THE INVENTION

5

Control device for controlling electromedical appliances

10

DESCRIPTION[0001] Control Device For Controlling Electromedical AppliancesCROSS-REFERENCE TO RELATED APPLICATIONS

15

[0002] This application is a section 371 of International Application No. PCT/EP2004/012261, filed October 29, 2004, which was published in the German language on May 12, 2005, under International Publication No. WO 2005/043569 A1 and the disclosure of which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

[0003] The invention relates to a control device for controlling electromedical appliances or groups of such appliances.

20

[0004] In order to control electromedical appliances, such as HF generators, laser equipment, surgical instruments employing water jets or similar apparatus used in particular in an operating theater, it is necessary for switching means to be employed, in particular by the surgeon, to control the function of the attached appliances or groups thereof according to the momentary requirements. For example, to stop bleeding an APC (argon-plasma coagulation) instrument is used, in which case actuation of a pedal switch on one hand opens a valve in order to deliver argon to a probe (and thus to the treatment site) and on the other hand to drive an HF generator in such a way that a high-frequency current flows from an electrode in the probe to the tissue while ionizing the argon, so that the tissue is coagulated. With the same device another function can also be performed, for which purpose the HF generator is switched into another mode of operation. All these control functions can be initiated with one switch, but usually several switches, which are often designed to be pressed by

25

30

hand or foot. When several such push-buttons or pedals are needed to control one or more appliances or groups thereof, each of these closed systems is connected to the associated appliances or groups thereof by means of a cable. Cable-free connections are also known, but even for these a special transmission pathway is assigned to each switching device. If it is desired for another function to be activatable at an appliance or group thereof, the appropriate switching means to support the function now desired must be newly installed, or another switching means must be appropriately altered and its connections rearranged. This is a complicated process.

[0005] Furthermore, in some circumstances a large number of cable connections are needed, and this situation causes a considerable disturbance of the surgical procedures being carried out in the foreground, owing to both mechanical interference ("stumbling" over the cables) and electromagnetic interference caused by the many cables and control leads together acting as antennae. The alternative of replacing the many cables by many radio links in turn causes a large number of electromagnetic disturbances.

BRIEF SUMMARY OF THE INVENTION

[0006] It is the ~~objective~~ object of the invention to ~~develop a control device of the kind described above further in such a way as to increase its versatility while keeping the structure~~ provide a control device for controlling a plurality of electrochemical appliances that may include a group of said appliances that is versatile and structurally compact, with little possibility of disturbances.

[0007] This ~~objective~~ object is achieved by a control device for controlling a plurality of electromedical appliances or groups thereof that may include a group of said appliances that comprises at least two pedal switches or similar switching means to generate generating control signals for controlling to control the appliances or groups thereof, connecting means disposed on the switching means for connecting the switching means to one another, allocation means for allocating adapted to allocate to the control signals particular controlling functions with respect to the appliances or groups thereof, and information-transfer means adapted to transmit the control signals from the switching means to the appliances or groups thereof.

[0008] ~~A substantial point~~ The success of the invention resides in the fact that the switching means are no longer directly connected (and this includes even wireless connection of whatever kind) to the appliances or groups thereof, but rather the switching means are indirectly connected thereto by way of the allocation means, so that within the latter a particular control

function, designed for particular functions of the appliances or groups thereof, can be allocated to each switching means. In this way the informational content, so to speak, of the signals produced by the switching means can be changed without altering the switching means themselves. This makes it possible not only to change the function of already installed control devices, but also to couple to one another as many control devices as desired, producing what amounts to a "keyboard", in which the "significance of the keys" can be determined by the operator according to what is required.

[0009] The connecting means comprise a data bus designed so that after a plurality of switching means have been connected to one another, the control signals of all switching means are available at the data bus. This ensures in a simple manner that all signals from the switching means are made available simultaneously.

[0010] Each of the switching means in this case comprises two signal couplers, in particular plug-and-socket connectors, connected to the data bus in such a way that when several switching means are connected to one another in series, at least one of the signal couplers can be used to connect the data bus to the information-transfer means. As a result, an unlimited number of switching means can be plugged together to form a "keyboard".

[0011] The information-transfer means can be connected to the appliances or groups thereof by way of a lead. Alternatively it is possible to equip the information-transfer means with at least one transmitter that can be connected to the switching means, and to provide at least one receiver connected to the appliances or groups thereof, for wireless transmission of the control signals. This eliminates the risk of "stumbling" over wires.

[0012] As described above, the switching means can be connected directly to one another. In the case of mechanical connection, a base plate can be provided onto which the switching means are set. Alternatively it is possible to equip the base plate with intermediate connection means, by way of which the switching means can be connected to one another. Within this base plate, furthermore, the transmitter and/or power supply or the like can be disposed. Preferably coding means are provided so that switching means can be identified by the appliances or groups thereof, so that the appliances can recognize "by themselves" the switching means allocated to them, and malfunctions or incorrect combinations can be ruled out.

~~In the following the invention is explained in greater detail with reference to exemplary embodiments, as follows:~~

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0013] The foregoing summary, as well as the following detailed description of the invention,
will be better understood when read in conjunction with the appended drawings. For the purpose of
illustrating the invention, there are shown in the drawings embodiments which are presently
preferred. It should be understood, however, that the invention is not limited to the precise
5 arrangements and instrumentalities shown.

[0014] In the drawings:

[0015] Fig. 1 shows a group of pedal switches separated from one another;

[0016] Fig. 2 shows the group of switches according to Fig. 1 when they have been
plugged together;

10 [0017] Fig. 3 shows a group of pedal switches with a base plate,

[0018] Fig. 4 shows a group of pedal switches with wireless connection and

[0019] Fig. 5 is a schematic block diagram of one embodiment of the control device in
accordance with the invention.

[0020] In the following description, the same reference numerals are used for identical parts or
15 parts with identical actions.

DETAILED DESCRIPTION OF THE INVENTION

[0021] As is evident in Fig. 1, a group of pedal switches 10 is provided, each of which
comprises a multi-pole connecting means 20 and (on the opposite side of the housing, not shown) a
corresponding connecting means, so that the switching means 10 shown here as pedal switches can
20 be plugged together to form a group, as is shown in Fig. 2. In addition mechanical connections are
provided so that the group shown in Fig. 2, which comprises a total of four pedal switches, is firmly
interconnected mechanically and so can be manipulated as a unit. For connection to the appliances
that are to be controlled, which are described in greater detail below, a cable is provided to serve as
information-transfer means 40.

25 [0022] The embodiment shown in Fig. 3 differs from that according to Fig. 2 in that the pedal
switches 10 are connected to one another not directly but indirectly, by way of associated plug
connectors 11 in a base plate 50 that serves simultaneously as a pedestal for the group of pedal
switches. Here, again, the connection to the appliances that are to be controlled is brought about by a
cable 40.

30 [0023] The embodiment shown in Fig. 4 differs from that according to Figs. 1 and 2 in that
instead of a cable, the information-transfer means 40 is designed as a wireless transmitter, i.e. one
that transmits by radio or infrared signals. Within these transmission means a rechargeable power

source is also provided, so that the whole unit can easily be transported and set up at any desired sites, with no need for a cable to be attached. This embodiment, of course, can also be combined with that according to Fig. 3. In particular, for example, the wireless information-transfer means can be disposed within the base plate 50.

5 **[0024]** In Fig. 5 the electrical structure of the whole arrangement is shown in principle in a block diagram. It can be seen in this diagram that each of the switching means 10 comprises plug-and-socket connectors 11 and 12, which are correspondingly shaped so that an arbitrarily large number of switching means 10 can be arrayed side by side and electrically connected to one another. The information-transfer means 40 can then be plugged into the last (on the left, in Fig. 5) switching
10 means 10.

[0025] One of the items provided in each of the switching means 10 is a data bus 21, which on one hand accepts the information arriving at the plug-and-socket connector 12 from another plugged-in switching means 10 and passes it on to the plug-and-socket connector 11 (and ultimately to the information-transfer means 40), and on the other hand is connected to a signal-generating
15 means 13 so that by way of a switch 14, e.g. a pedal such as is shown in Figs. 1-4, switch signals are generated and sent on to the plug-and-socket connector 11. At the switching means 10 there are additionally provided allocation means 30, e.g. in the form of coding switches, by way of which particular functions can be assigned to the various switching means 10, with reference to appliances 1, 1' or appliance groups 2, which are to be controlled by way of the switching means 10.

20 **[0026]** The items of information transferred within the data bus 21 are conducted through the connectors 11 and 12 to a transmitter 41, the signals from which are received by a receiver 42, which together with the transmitter 41 constitutes the information-transfer means 40. It should be pointed out that instead of a wireless transmission of this kind, a cable can be used.

[0027] The above-mentioned allocation means 30 can also be disposed within the receiver 42, so
25 that for each switching means 10 the "content" of an item of switching information it has generated can also be sent on to a central site.

[0028] In addition, there is provided in the receiver 42 a coding means 43 designed so that the signals sent from the receiver 42 through the connecting cable 44 to the appliances 1, 1' or appliance groups 2 can carry out only the control functions that are permitted in those particular appliances or
30 appliance groups. It is likewise possible to use such coding in order to block certain combinations of functions, so that for instance it is impossible during an operation for a given appliance to be used simultaneously for rinsing and for conducting high-frequency current, since such current should be switched on only in combination with the delivery of an inert gas, when no rinsing fluid is present.

By this means, therefore, it is simultaneously possible to eliminate malfunction owing to errors made by the person operating the switching means 10.

100291 It will be evident from the above that an essential point of the present invention resides in the fact that the switching means 10 are initially not specified for particular functions, and the allocation of functions (including protection against malfunctions) is brought about by the allocation means 30 and the coding means 43 (centrally or at each switching means 10).

List of reference numerals

	1,1' Appliance
10	2 Group of appliances
	10 Switching means
	11 Plug and socket connector
	12 Plug and socket connector
	13 Signal generating means
15	14 Switch
	20 Connecting means
	21 Data bus
	30 Allocation means
	40 Information transfer means
20	41 Transmitter
	42 Receiver
	43 Coding means
	44 Connection cable
	50 Base plate
25	

[0030] It will be appreciated by those skilled in the art that changes could be made to the embodiments described above without departing from the broad inventive concept thereof. It is understood, therefore, that this invention is not limited to the particular embodiments disclosed, but it is intended to cover modifications within the spirit and scope of the present invention as defined by the appended claims.

5

CLAIMS

We claim:

1. (Currently Amended) Control device for controlling a plurality of electromedical appliances that may include a group of said appliances comprising

5 ~~1. Control device for controlling electromedical appliances (1, 1') or appliance groups (2), comprising~~
~~at least two pedal switches or similar~~ at least two switching means (10) for
generating control signals to control ~~the~~ said appliances (1, 1') or appliance groups
(2),

10 ~~plug and socket connectors or similar,~~

~~connecting means (20) disposed on the~~ said switching means (10), by way of
~~which the~~ connecting said switching means (10) can be connected to one another,

~~allocation means (30) adapted to allocate to the~~ said control signals particular

15 ~~controlling functions with reference to the~~ said appliances (1, 1') or appliance groups
(2), and

~~information-transfer means (40) adapted to transmit the~~ said control signals from
~~the~~ said switching means (10) to ~~the~~ said appliances (1, 1') or appliance groups
20 (2).

2. 2. (Currently Amended) Control device according to Claim 1,
~~characterized in that the~~ wherein said connecting means (20) comprise a data bus
(21) ~~designed so~~ adapted such that ~~after~~ when a plurality of said switching means (10)
have ~~been~~ are connected to one another, the control signals of all said switching means (10) are
25 available at ~~the~~ said data bus (21).

3. 3. (Currently Amended) Control device according to one of the preceding
claims,

~~characterized in that~~ claim 2, wherein each of ~~the~~ said switching means (10)
comprises two signal couplers (11, 12), ~~in particular plug and socket~~

30 ~~connectors,~~ that are connected to the data bus (21) ~~in such a way that when~~ said
switching means (10) are connected together in series, ~~the~~ said data bus (21) can be connected

to ~~the~~said information-transfer means (40) ~~by way~~means of at least one of the signal couplers (11, 12).

4. 4. (Currently Amended) ~~Control device according to one of the preceding~~
~~claims,~~

5 ~~characterized in that the~~claim 1, wherein said information-transfer means (40)
comprise at least one transmitter (41) ~~that can be connected to the~~said switching means
(10) and at least one receiver (42) ~~connected to the~~said appliances (1, 1') ~~or~~
appliance groups (2), for wireless transmission of ~~the~~said control signals.

10 5. 5. (Currently Amended) ~~Control device according to one of the preceding~~
~~claims,~~
~~characterized by~~claim 1, comprising a base plate (50) ~~on~~on which ~~the~~said switching
means (10) ~~can be~~is set.

6. 6. (Currently Amended) ~~Control device according to Claim 5,~~
~~characterized in that the~~wherein said base plate (50) comprises intermediate
15 connecting means (11) ~~by way of which the~~to connect said switching means (10) ~~can~~
~~be connected to one another.~~

7. 7. (Currently Amended) ~~Control device according to one of the preceding~~
~~claims,~~
~~characterized by~~claim 1, comprising coding means (43) ~~for the identification~~
20 ~~of that identify said~~ switching means (10) ~~by the appliances (1, 1') or appliance~~
~~groups (2).~~

